

FEDERAL COMMUNICATIONS COMMISSION

FM BROADCAST STATION LICENSE



Official Mailing Address:

HUDSON GROUP LTD. PARTNERSHIP OF PA
P. O. BOX 3433
HARRISBURG, PA 17105

Authorizing Official:

Deborah Price

Deborah Price
Supr Applications Examiner, FM Branch
Audio Services Division
Mass Media Bureau

Grant Date: December 16, 1985

Call sign: WIMX

This license expires 3:00 am.
local time: August 01, 1991

License File No.: BLH-850513KJ

This license covers Permit No.: 841108IA

This authorization re-issued to reflect a call sign change from
WHIT-FM to WIMX effective 4/04/88.

Subject to the provisions of the Communications Act of 1934,
subsequent acts and treaties, and all regulations heretofore or
hereafter made by this Commission, and further subject to the
conditions set forth in this license, the licensee is hereby
authorized to use and operate the radio transmitting apparatus herein
described.

This license is issued on the licensee's representation that the
statements contained in licensee's application are true and that the
undertakings therein contained so far as they are consistent herewith,
will be carried out in good faith. The licensee shall, during the term
of this license, render such broadcasting service as will serve the
public interest, convenience, or necessity to the full extent of the
privileges herein conferred.

This license shall not vest in the licensee any right to operate the
station nor any right in the use of the frequency designated in the
license beyond the term hereof, nor in any other manner than
authorized herein. Neither the license nor the right granted hereunder
shall be assigned or otherwise transferred in violation of the
Communications Act of 1934. This license is subject to the right of
use or control by the Government of the United States conferred by
Section 606 of the Communications Act of 1934.

Name of Licensee:

HUDSON BROADCASTING CORP.

Call sign: WIMX

License No.: BLH-850513KJ

Station Location:

PA-HARRISBURG

Frequency (MHz): 99.3

Channel: 257

Class: A

Hours of Operation: Unlimited

Main Studio Address:

PA-HARRISBURG

Transmitter location (address or description):

360 POPLAR CHURCH, WORMLEYBURG, PENNSYLVANIA

Remote control point address:

PA-HARRISBURG

Transmitter: Type accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power (kW): 4.2

Antenna type: (directional or non-directional): Non-directional

Desc: SEE CONDTION

Antenna coordinates: North Latitude: 40 15 44.0
West Longitude: 76 54 37.0

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the horizontal plane (kW) :	3.00	3.00
Height of radiation center above ground (meters) :	118.0	118.0
Height of radiation center above mean sea level (meters) :	240.0	240.0

Height of radiation center above
average terrain (meters) : 100.0 100.0

Overall height of antenna structure above ground (including obstruction
lighting, if any) : 122.0 meters

Obstruction marking and lighting specifications for antenna
structure:

It is to be expressly understood that the issuance of these specifications
is in no way to be considered as precluding additional or modified marking
or lighting as may hereafter be required under the provisions of Section
303(q) of the Communications Act of 1934, as amended.

Paragraph 1.0, FCC Form 715 (March 1978):

Antenna structures shall be painted throughout their height with
alternate bands of aviation surface orange and white, terminating with
aviation surface orange bands at both top and bottom. The width of the
bands shall be equal and approximately one-seventh the height of the
structure, provided however, that the bands shall not be more than 100
feet nor less than 1 and 1/2 feet in width. All towers shall be
cleaned and repainted as often as necessary to maintain good
visibility.

Paragraph 3.0, FCC Form 715 (March 1978):

There shall be installed at the top of the structure one 300 m/m
electric code beacon equipped with two 620- or 700-watt lamps (PS-40,
Code Beacon type), both lamps to burn simultaneously, and equipped
with aviation red color filters. Where a rod or other construction of
not more than 20 feet in height and incapable of supporting this
beacon is mounted on top of the structure and it is determined that
this additional construction does not permit unobstructed visibility
of the code beacon from aircraft at any normal angle of approach,
there shall be installed two such beacons positioned so as to insure
unobstructed visibility of at least one of the beacons from aircraft
at any normal angle of approach. The beacons shall be equipped with a
flashing mechanism producing not more than 40 flashes per minute nor
less than 12 flashes per minute with a period of darkness equal to
approximately one-half of the luminous period.

Paragraph 12.0, FCC Form 715 (March 1978):

On levels at approximately two-thirds and one-third of the over-all height of the tower, there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of at least one light at each level from aircraft at any normal angle of approach.

Paragraph 21.0, FCC Form 715 (March 1978):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

Special operating conditions or restrictions:

ANTENNA: COLLINS LPC-@ TWO SECTIONS CIRCULARLY POLARIZED
SIDE-MOUNTED AT THE 118 METER LEVEL (C/R-AGL) ON A MAST
MOUNTED ON A GUYED TOWER.